

BEACON HILL™ FLAGSTONE 60mm

ENDURACOLOR™



ALMOND GROVE FUSION



FOSSIL



GRANITE MIST



TUSCANY

44
SRI

VISUAL APPEARANCE

Gentle surface clefts and clean edges.

FINISH

Flag/Riven finish.

PRODUCT SPECIFICATIONS



LARGE RECTANGLE
15 x 22½ x 2⅜"
380 x 570 x 60 mm




SQUARE
15 x 15 x 2⅜"
380 x 380 x 60mm



SMALL RECTANGLE
7½ x 15 x 2⅜"
190 x 380 x 60mm

3 UNIT RANDOM BUNDLE

EDGE DETAIL




ROUNDED EDGE


BUNDLE CONFIGURATION



LAYING PATTERNS



BHF RANDOM A
40% Large Rectangle, 40%
Square, 20% Small Rectangle



BHF RANDOM B
40% Large Rectangle, 40%
Square, 20% Small Rectangle

*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C936 Standard Specifications for Solid Concrete Interlocking Paving Units


Conforms to:

- C140 for Absorption 4% avg - 5% max
- C140 for Compressive Strength > 8,000 PSI avg.
- C1645 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

Product	Solar Reflectance	SRI
Tuscany	0.39	44 

LEED INFORMATION

Materials & Resources: LEED V4:

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour

PEDESTRIAN FRIENDLY

Not recommended for vehicular




PRODUCT DATA

Stones & Bundling	Unit Thickness	SqFt Per				Per Bundle		Soldier LnFt Per			Sailor LnFt per			Units Per		Lbs Per		
		Bundle	Layer	Section	Stone	Layers	Sections	Unit	Layer	Bundle	Unit	Layer	Bundle	SqFt	Bundle	Layer	Section	Bundle
Fossil and Granite Mist manufactured in Ayr / All other colours manufactured in Pickering																		
Random Bundle		104.91	11.66	-	-	9	-	-	-	-	-	9.35	84.15	0.69	72	319.93	-	2,879.4
Large Rectangle	2%* (60mm)	-	4.66	-	2.331	-	-	-	-	-	1.87	-	33.66	0.48	18	-	-	-
Small Rectangle	2%* (60mm)	-	4.66	-	0.777	-	-	-	-	-	0.63	-	16.83	1.43	27	-	-	-
Square	2%* (60mm)	-	2.33	-	1.554	-	-	-	-	-	1.25	-	33.66	0.72	27	-	-	-

Notes: Sold in full bundles only on a refundable skid. **Beacon Hill 60mm is not intended for vehicular applications.** All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



RECOMMENDED SANDS		RECOMMENDED SEALER																			
 <p>Romex: Rompox™ ECO-Fine Pedestrian Applications only Vehicular when laid on a Trass Bed</p> <ul style="list-style-type: none"> Ready mixed and easy to use Resin film free Resistant to ants, weeds, de-icing salts Made from 98% natural, recycled or renewable raw materials Pressure washer safe Ideal for joint widths from 5mm (1/4") <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>5-6mm Joints</th> </tr> </thead> <tbody> <tr> <td>Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can</td> <td>125 sqft / 55 lb mix</td> </tr> </tbody> </table>	Colour	5-6mm Joints	Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix	 <p>Alliance - Gator G2 MAXX Sand</p> <ul style="list-style-type: none"> Rain safe after 15 minutes (24hr no rain if concrete overlay) Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation Dust free and haze free Requires only one watering <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>Narrow Joints</th> <th>Wide Joints</th> </tr> </thead> <tbody> <tr> <td>Beige, Grey, Ivory 50 lb bag</td> <td>65-85 sqft</td> <td>22-42 sqft</td> </tr> <tr> <td>Black 50 lb bag</td> <td>58-76 sqft</td> <td>20-38 sqft</td> </tr> </tbody> </table>	Colour	Narrow Joints	Wide Joints	Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft	Black 50 lb bag	58-76 sqft	20-38 sqft	 <p>Alliance - Gator Natural Look Sealer</p> <ul style="list-style-type: none"> Water-based Zero gloss finish Multi purpose Rain safe after 24 hours <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Size</th> <th>Area</th> </tr> </thead> <tbody> <tr> <td>3.78 L / 1 U.S. gal.</td> <td>175 sqft</td> </tr> <tr> <td>18.9 L. / 5.28 U.S. gal.</td> <td>875 sqft</td> </tr> </tbody> </table>	Size	Area	3.78 L / 1 U.S. gal.	175 sqft	18.9 L. / 5.28 U.S. gal.	875 sqft
Colour	5-6mm Joints																				
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix																				
Colour	Narrow Joints	Wide Joints																			
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft																			
Black 50 lb bag	58-76 sqft	20-38 sqft																			
Size	Area																				
3.78 L / 1 U.S. gal.	175 sqft																				
18.9 L. / 5.28 U.S. gal.	875 sqft																				

*Please refer to Sands & Sealers on pages 190-202 for more detailed information.
 Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.