


# Melville® 60 Small Rectangle Paver




- Do not use vibrating plate
- Techniseal** 1 bag of sand covers approx. 103 ft<sup>2</sup>
- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic


## Melville® 60 Small Rectangle Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
	60 x 190 x 380	2 3/8 x 7 1/2 x 15			
Weight/unit	10 kg	22 lb	<b>PRESTIGE COLOURS</b>		
Unit/surface	13.89 unit/m <sup>2</sup>	1.29 unit/ft <sup>2</sup>	12053044	Range Amber Beige (1)	
Area/layer	0.87 m <sup>2</sup>	9.33 ft <sup>2</sup>	12052446	Rockland Black (1)	
<b>Area/cube</b>	<b>10.44 m<sup>2</sup></b>	<b>111.96 ft<sup>2</sup></b>	12052448	Range Scandina Grey (2)	
Length/row Soldier	2.28 lin. m	7.48 lin. ft	<b>STANDARD COLOUR</b>		
Length/cube Soldier	27.36 lin. m	89.76 lin. ft	12053043	Range Shaded Grey (1)	
Qty/cube	144 units	144 units	Sold in full cubes only		
Weight/cube	1465 kg	3225 lb	Production locations:		
			(1) Québec		
			(2) Cambridge		

### LAYING PATTERNS



Linear



Herringbone

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville 60 Small Rectangle Paver</b>	CSA A231.1	μ 50 MPa ≥ 45 MPa	N/A	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

\* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Sand compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. The Melville 60 slab is compatible with the Melville 60 small rectangle paver for non-vehicular application only.