



BURGUNDY RED



BURNT CLAY



BASALT



OLD OAK



3 COLOUR BLEND

Sold separately / Blended on site

## VISUAL APPEARANCE

Inspired by the rich colour and timeworn beauty of European street pavers.

## FINISH

Timeworn. Realta™ Technology provides ultra-realistic textures cast from brick, cobblestone or flagstone.

## PRODUCT SPECIFICATIONS



### STANDARD

2½ x 7⅞ x 2⅜"


65 x 200 x 60mm

## EDGE DETAILS




ROUNDED EDGE


## LAYING PATTERNS



COPTHORNE A  
100% Standard



COPTHORNE B  
100% Standard



COPTHORNE C  
100% Standard

\*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

**ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units**

Conforms to:

- C140 for Absorption 5% avg - 7% max
- C140 for Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3 mm**

*Test results available upon request*

**Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines**

LEED INFORMATION

**Materials & Resources: LEED V4:**

- Building Product Disclosure and Optimization
- Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**
- Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**
- Material Ingredient Reporting - Material Ingredient Reporting • **1 point**
- Material Ingredient Reporting - Material Ingredient Optimization • **1 point**
- Environmental Product Declaration • **1 point**

TECHNICAL ADVANTAGES

**ELEGANCE**

Deep rich colours and unique textures

**REALA™**

Cast from historic brick

**ULTIMA™**

Up to 4x stronger than poured-in-place concrete

**DRIVE FRIENDLY**

Can handle vehicular loads

*Ask about our base stabilization system*

PRODUCT DATA

Stones & Bundling	Unit	SqFt Per				Per Bundle	Soldier LnFt Per			Sailor LnFt per			Units Per			Lbs Per			
	Thickness	Bundle	Layer	Section	Stone	Layers	Unit	Layer	Bundle	Unit	Layer	Bundle	SqFt	Section	Bundle	Layer	Section	Bundle	
<b>Ayr Manufacturing</b>																			
Standard	2 3/8" (60mm)	89.20	11.15	-	0.15	8	0.21	-	127.95	0.66	-	393.75	6.73	-	600	294	-	2,349	

Notes: Sold in full bundles only on a refundable skid. All measurements are nominal. **Important: A urethane rubber paver mat must be used to prevent scuffing.** For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



Pedestrian



Residential Vehicular






Commercial Vehicular



Borders and Accents

\*Wall pairing suggestion- U-CARA\*

RECOMMENDED SANDS			RECOMMENDED SEALER																						
 <p><b>Romex: Rompox® ECO-Fine</b> Pedestrian Applications only Vehicular when laid on a Trass Bed</p> <ul style="list-style-type: none"> <li>  Ready mixed and easy to use</li> <li>  Resin film free</li> <li>  Resistant to ants, weeds, de-icing salts</li> <li>  Made from 98% natural, recycled or renewable raw materials</li> <li>  Pressure washer safe</li> <li>  Ideal for joint widths from 5mm (1/4")</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>5-6mm Joints</th> </tr> </thead> <tbody> <tr> <td>Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can</td> <td>125 sqft / 55 lb mix</td> </tr> </tbody> </table>			Colour	5-6mm Joints	Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix	 <p><b>Alliance - Gator G2 MAXX Sand</b></p> <ul style="list-style-type: none"> <li>  Rain safe after 15 minutes (24hr no rain if concrete overlay)</li> <li>  Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation</li> <li>  Dust free and haze free</li> <li>  Requires only one watering</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Colour</th> <th>Narrow Joints</th> <th>Wide Joints</th> </tr> </thead> <tbody> <tr> <td>Beige, Grey, Ivory 50 lb bag</td> <td>65-85 sqft</td> <td>22-42 sqft</td> </tr> <tr> <td>Black 50 lb bag</td> <td>58-76 sqft</td> <td>20-38 sqft</td> </tr> </tbody> </table>			Colour	Narrow Joints	Wide Joints	Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft	Black 50 lb bag	58-76 sqft	20-38 sqft	 <p><b>Alliance - Gator Seal Satin Look</b></p> <ul style="list-style-type: none"> <li>  Solvent-based</li> <li>  Low gloss finish</li> <li>  Vibrant colour enhancer</li> <li>  Rain safe after 90 minutes</li> <li>  Helps resist corrosion from de-icing salt, ultra-violet rays effects, motor oils and grease stains</li> </ul> <p>Coverage:</p> <table border="1"> <thead> <tr> <th>Size</th> <th>Area</th> </tr> </thead> <tbody> <tr> <td>3.78 L / 1 U.S. gal.</td> <td>175 sqft</td> </tr> </tbody> </table>			Size	Area	3.78 L / 1 U.S. gal.	175 sqft
Colour	5-6mm Joints																								
Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can	125 sqft / 55 lb mix																								
Colour	Narrow Joints	Wide Joints																							
Beige, Grey, Ivory 50 lb bag	65-85 sqft	22-42 sqft																							
Black 50 lb bag	58-76 sqft	20-38 sqft																							
Size	Area																								
3.78 L / 1 U.S. gal.	175 sqft																								

\*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.