


City Slab



Do not use vibrating plate



Techniseal 1 bag of sand covers approx. 147 ft²



Pedestrian - Designed to withstand pedestrian traffic



Roof-top patio - Designed to be installed on pedestals


City 500 x 750 Slab




	DIMENSIONS (MM)	DIMENSIONS (IN)
C	60 x 500 x 750	23/8x1911/16x291/2
Weight/unit	52 kg	114 lb
Surface/unit	0.38 m ²	4.04 ft ²
Area/layer	0.75 m ²	8.07 ft ²
Area/cube	9.00 m²	12 Rows 96.84 ft²
Qty/cube	24 units	24 units
Weight/cube	1270 kg	2800 lb

CODES	COLOURS
PRESTIGE COLOURS	
12051210	Cameo Beige
STANDARD COLOURS	
12059437	Alpine Grey
12059443	Sterling Grey
Sold by layer	
Production location St-Eustache	


TYPICAL ROW



LAYING PATTERNS



Linear
100 % C



Herringbone
100 % C

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
City Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches.

Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material. Given the weight of this slab, it is highly recommended to use suction-based lifting equipment for handling and placement (avoid manual installation).

This product can be installed on pedestals for a rooftop application. It can safely withstand a load of up to 300 kg.